

UL 1015 Hook Up Wire 连接线



Description

- Rated temperature: 105°C
- Rated voltage: 600V
- Reference standard: UL Subject 758, UL1581
- Tinned or bare, stranded or solid copper conductor
- Colour-coded PVC insulation
- Uniform insulation thickness to ensure easy stripping and cutting
- Passes UL VW-1 & CSA FT1 vertical flame test

说明

- 额定温度：105°C
- 额定电压：600V
- 标准：UL758,UL1581
- 导体使用单根或绞合裸铜或镀锡铜线
- 聚氯乙烯绝缘
- 绝缘厚度均匀,方便剥皮及剪裁
- 通过UL VW-1及CSA Ft1垂直耐燃测试

Application

For internal wiring of electronic and electrical equipment

应用

用于电子, 电器设备内部连线

No. 编号	Conductor 导体		Insulation 绝缘		Max. Resistance at 20°C 最大导体电阻 (Ω/km)	Re. weight 参考重量 Kg/Km
	AWG 规线	No./mm 根数/线径	Nom. Thick 厚度/mm	Nom. Dia. 外径/mm		
U50126A	26	7/0.16	0.82	2.12	139	6.3
U50124A	24	11/0.16	0.79	2.19	88.9	7.2
U50122A	22	17/0.16	0.82	2.40	57.5	9.3
U50120A	20	26/0.16	0.82	2.58	34.6	11.5
U50118A	18	34/0.18	0.82	2.80	3.3	15.1
U50117A	17	42/0.18	0.79	2.92	17.4	17.6
U50116A	16	26/0.254	0.79	3.08	15.1	20.5
U50114A	14	41/0.254	0.79	3.46	9.2	28.9
U50112A	12	65/0.254	0.79	3.94	5.4	41.3
U50110A	10	66/0.32	0.79	4.56	4.1	61.2

UL Appliance wiring
Material Reference Table
标准电线电缆