

UL 1007 Hook Up Wire 连接线



Description

- Rated temperature: 80°C
- Rated voltage: 300V
- Reference standard: UL Subject 758, UL1581
- Tinned or bare, stranded or solid copper conductor
- Color-coded lead free PVC insulation
- Uniform insulation thickness to ensure easy stripping and cutting
- Passed UL VW-1 & CSA FT1 vertical flame test

说明

- 额定温度：80℃
- 额定电压：300V
- 标准：UL758,UL1581
- 导体使用单根或绞合裸铜或镀锡铜线
- 无铅聚氯乙烯绝缘
- 绝缘厚度均匀,方便剥皮及剪裁
- 通过UL VW-1及CSA FT1垂直耐燃测试

Application

For internal wiring of electronic and electrical equipment

应用

用于电子, 电器设备内部连线

No. 编号	Conductor 导体		Insulation 绝缘		Max. Resistance at 20°C 最大导体电阻 (Ω/km)	Re. weight 参考重量 Kg/Km
	AWG 规线	No./mm 根数/线径	Nom. Thick 厚度/mm	Nom. Dia. 外径/mm		
U70130A	30	7/0.1	0.41	1.12	354	1.9
U70128A	28	7/0.27	0.41	1.20	223	2.5
U70126A	26	7/0.16	0.41	1.30	139	3.1
U70124A	24	11/0.16	0.41	1.43	88.9	4.0
U70122A	22	17/0.16	0.41	1.58	57.5	5.4
U70120A	20	26/0.16	0.41	1.76	34.6	7.5
U70118A	18	41/0.16	0.41	2.00	23.3	10.7
U70116A	16	26/0.254	0.41	2.32	15.1	15.8

UL Appliance wiring
Material Reference Table
标准电线/电缆